

SELF CENTERING CHUCKS - Gripping Capacity & Safe Revolutions Per Minute - RPM

Size in mm	A		B		C		D		E		RPM (Maximum)	
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Cast Iron Body	Steel Body
60	1	16	20	33	35	50	20	35	30	50	3500	4500
80	2	27	22	45	40	69	24	50	40	71	3000	4000
100	3	33	25	60	55	87	32	70	60	93	2500	3800
125	3	42	34	80	70	112	38	90	80	120	2000	3200
160	3	68	42	105	90	154	48	110	100	160	1700	2500
180	4	75	45	115	95	175	52	120	105	180	1500	2300
190	4	80	48	125	100	180	56	130	115	190	1400	2100
200	4	90	52	130	110	194	60	140	120	200	1300	2000
230	5	100	56	150	115	220	65	155	135	230	1200	1800
250	5	110	62	165	120	240	75	170	145	250	1100	1600
270	7	130	70	185	135	260	85	195	155	270	1000	1500
315	10	180	80	210	150	300	96	225	165	315	800	1300
355	15	190	90	230	160	335	105	240	170	355	770	1200
375	20	200	100	240	180	355	120	260	180	375	750	1150
400	20	200	100	260	190	380	120	290	205	400	700	1000
460	30	230	120	280	210	430	135	330	230	460	600	900
500	35	260	135	300	225	480	155	370	265	500	500	800
610	50	350	170	400	245	580	170	470	365	610	400	700

INDEPENDENT CHUCKS - Gripping Capacity & Safe Revolutions Per Minute - RPM

Size in mm	80	100	125	160	200	250	305	350	400	450	510	610
Minimum Capacity	3	4	4	6	12	18	18	18	25	25	55	55
Maximum Capacity	80	100	125	160	200	250	305	350	400	450	510	610
RPM Cast Iron Body	1200	1200	1200	1200	1200	1100	900	800	700	600	500	400
RPM STEEL Body	1700	1700	1700	1700	1700	1500	1200	1100	950	800	700	550

All Dimensions are in Millimetres unless specified